



### Features

- ✔ 8 relay outputs, 5A

## Output module digital for 300 8x Relai

Digital output modules for the 300 series

The module has 8x relay outputs.

### General information

Order number	700-322-1HF20
Article name	DEA 300, relay, quenching circuit, 8 outputs
Scope of delivery	DEA 300, relay, quenching circuit, 8 outputs
Dimensions (DxWxH)	116 x 40 x 125 mm
Weight	Approx. 300g
Number of outputs	8
Isolation from the backplane bus	Yes (optocoupler)
Load voltage L+/L-	DC 24 V
Front connectors	40-pin

### Output voltage

AC to	230 V
DC to	120 V
Total current of the outputs (per group)	Max. 5 A

### Switching frequency of the outputs

Under resistive load max.	2 Hz
---------------------------	------

Under inductive load max.	0.5 Hz
Under lamp load max.	2 Hz

### Switching capacity of the contacts

Under resistive load max.	8 A (AC 230 V)
	8 A (DC 24 V)
Under inductive load max.	3 A (AC 230 V)
	2 A (DC 24 V)

### Switching operations of the contacts

Under mechanical load	10 million
Under resistive load	5 A, 0.2 million

### Ambient conditions

Ambient temperature	0 °C ... +60 °C
Transport and storage temperature	-25 °C ... +75 °C
Pollution degree	2
Protection rating	IP20
Approvals	CE

