



## Features

- ✓ Metalized housing
- ✓ No parts that can be lost
- ✓ Integrated switchable terminating resistor
- ✓ Axial cable outlet
- ✓ Proven screw terminal
- ✓ The PROFIBUS connectors are also available in packs of 10 or 50
- ✓ The maximum ambient temperature for UL is +60 °C

## PROFIBUS Connector 180° Screwterminal

**PROFIBUS connector - proven and worldwide in use.**

The PROFIBUS connector with axial cable outlet is equipped with a proven and reliable

screw terminal.

It is quickly mounted and has integrated, connectible terminating resistors.

For improved EMC compatibility, the housing

of the plug is metalized.

The PROFIBUS connector works in the extended ambient temperature range of -25 °C to +85 °C.

### General information

Order number	700-972-0CA12
Article name	PROFIBUS connector, axial, screw terminal
Scope of delivery	PROFIBUS connector, installation instructions
Dimensions (DxWxH)	68 x 35 x 17 mm
Weight	Approx. 40 g
Cable outlet	Axial cable outlet, suitable for FastConnect stripping tool
Terminating resistor	Resistor combination integrated and switchable using slide switch
PG connection socket	No
PROFIBUS bus cable	60/75 °C copper cable up to 1.0 mm <sup>2</sup>
Maximum outside diameter	8.0 mm
Voltage supply	+4.75 ... +5.25 V DC (must come from the device)
Current draw	Max. 12.5 mA

### PROFIBUS interface

Number	1
--------	---

Transmission rate	max. 12 Mbps
Connection	SUB-D connector, 9-pin
Connection	SUB-D connector, 9-pin

### Connector

Connector type	terminal strips
Number	4
Number	4

### Ambient conditions

Ambient temperature	-25 °C ... +85 °C (The maximum ambient temperature for UL is +60 °C.)
Transport and storage temperature	-25 °C ... +85 °C
Relative air humidity	70 % at +25 °C
Pollution degree	2
Protection rating	IP20
Approvals	CE, UL

© Helmholtz GmbH & Co. KG | Hannberger Weg 2 | 91091 Großenseebach | Germany  
Phone +49 9135 7380-0 | Fax +49 9135 7380-110 | info@helmholtz.com | www.helmholtz.com

We reserve the right to make changes without notice.  
Errors and omissions excepted.