



## PROFIBUS connector, 90°, EasyConnect®, diagnostics LED

with PG

- 3 status LEDs to indicate “bus operation,” “participant is sending,” “terminating resistor inserted”
- Metalized housing
- No parts that can be lost
- Integrated switchable terminating resistor
- 90° cable outlet
- Quick-connect technology EasyConnect®
- Visual connection control
- The PROFIBUS connectors are also available in packs of 10 or 50
- The maximum ambient temperature for UL is +60 °C
- Integrated PG interface

With the aid of a visual connection control, it is also possible to check that the PROFIBUS cable is correctly connected after it is mounted. For improved EMC compatibility, the housing of the plug is metalized. Using the PROFIBUS connector diagnosis, a PROFIBUS network can be established in which the user can at any time check the state of the bus system at a glance. The three built-in LEDs with the easily distinguished colors blue, green, and orange indicate the most important states of the PROFIBUS network at each station. The state of the terminating resistor (orange), whether bus activity is present (green), and whether the addressed participant is participating in the bus traffic (blue) are displayed. In this way you can immediately recognize error states such as bus interrupts, missing or incorrectly connected terminating resistors, and malfunctioning or failed bus participants. The EasyConnect® connector works in the extended ambient temperature range of -25 °C to +85 °C.

Additional participants can be connected via the integrated PG interface.

### Technical specifications

<b>General information</b>	
Order number	700-972-7BB50
Article name	PROFIBUS connector, 90°, EasyConnect®, diagnostics LED, with PG
Scope of delivery	PROFIBUS connector, installation instructions
Dimensions (DxWxH)	72 x 40 x 17 mm
Weight	Approx. 40 g
<b>Cable outlet</b>	Vertical cable outlet, suitable for FastConnect stripping tool
<b>PROFIBUS interface</b>	
Number	1
Transmission rate	max. 12 Mbps
Connection	SUB-D connector, 9-pin
<b>Terminating resistor</b>	Resistor combination integrated and switchable using slide switch
<b>PROFIBUS bus cable</b>	FC standard cable, rigid or flexible; 0.64 mm Ø, 60/75 °C copper cable
<b>Connector type</b>	EasyConnect®

<b>Status indicator</b>	1 LED, 3-color
<b>Voltage supply</b>	+4.75 ... +5.25 V DC (must come from the device)
<b>Current draw</b>	Max. 35 mA
<b>Ambient conditions</b>	
Ambient temperature	-25 °C ... +85 °C( The maximum ambient temperature for UL is +60 °C.)
Transport and storage temperature	-25 °C ... +85 °C
Relative air humidity	70 % at +25 °C
Pollution degree	2
Protection rating	IP20
Certifications	CE, UL
<b>CE</b>	
RoHS	Yes
REACH	Yes