



PROFIBUS connector, 35°, screw terminal without PG

- Metalized housing
- No parts that can be lost
- Integrated switchable terminating resistor
- 35° cable outlet
- Proven screw terminal
- The PROFIBUS connectors are also available in packs of 10 or 50
- The maximum ambient temperature for UL is +60 °C.

It is quickly mounted and has integrated, connectable terminating resistors. For improved EMC compatibility, the housing of the plug is metalized. The PROFIBUS connector works in the extended ambient temperature range of -25 °C to +85 °C.

Technical specifications

General information	
Order number	700-972-0BA41
Article name	PROFIBUS connector, 35°, screw terminal, without PG
Scope of delivery	PROFIBUS connector, installation instructions
Dimensions (DxWxH)	54 x 40 x 17 mm
Weight	Approx. 40 g
Cable outlet	35° angled cable outlet
PROFIBUS interface	
Number	1
Transmission rate	max. 12 Mbps
Connection	SUB-D connector, 9-pin
Terminating resistor	Resistor combination integrated and switchable using slide switch
PG connection socket	No
PROFIBUS bus cable	60/75 °C copper cable up to 1.0 mm ²
Connector	
Connector type	terminal strips
Number	4
Maximum outside diameter	8.0 mm
Voltage supply	+4.75 ... +5.25 V DC (must come from the device)
Current draw	Max. 12.5 mA
Ambient conditions	
Ambient temperature	-25 °C ... +85 °C (The maximum ambient temperature for UL is +60 °C.)
Transport and storage temperature	-25 °C ... +85 °C

Relative air humidity	70 % at +25 °C
Pollution degree	2
Protection rating	IP20
Certifications	CE, UL
CE	
RoHS	Yes
REACH	Yes