



Features

- ✓ Metalized housing
- ✓ No parts that can be lost
- ✓ Integrated switchable terminating resistor
- ✓ 90° cable outlet
- ✓ Proven screw terminal
- ✓ The PROFIBUS connectors are also available in packs of 10 or 50
- ✓ The maximum ambient temperature for UL is +60 °C.
- ✓ Integrated PG interface

PROFIBUS Connector with Diagnostics LED 90° EasyConnect® with PG M12-Connector

PROFIBUS connector - proven and worldwide in use.

Through the use of pre-assembled system cables, connection errors are excluded. Installation costs are reduced to a minimum.

The connector has two M12 connections and integrated terminating resistors. For improved electromagnetic compatibility, the housing is metalized.

The PROFIBUS connector works in the

extended ambient temperature range of -25 °C to +85 °C.

Additional participants can be connected via the integrated PG interface.

General information

Order number	700-974-0BB12
Article name	PROFIBUS connector, 90° M12, with PG
Scope of delivery	PROFIBUS connector, installation instructions
Dimensions (DxWxH)	41 x 17 x 70 mm
Weight	Approx. 60 g
Cable outlet	Vertical cable outlet
Terminating resistor	Resistor combination integrated and switchable using slide switch
PG connection socket	yes, SUB-D, 9-pin
Connector type	M12
Voltage supply	+4.75 ... +5.25 V DC (must come from the device)
Current draw	Max. 12.5 mA

PROFIBUS interface

Number	1
Transmission rate	max. 12 Mbps
Connection	SUB-D connector, 9-pin

Ambient conditions

Ambient temperature	-25 °C ... +85 °C (The maximum ambient temperature for UL is +60 °C.)
Transport and storage temperature	-25 °C ... +85 °C
Relative air humidity	70 % at +25 °C
Pollution degree	2
Protection rating	IP20
Approvals	CE, UL