



Features

- ✓ 110–230 V AC input voltage
- ✓ Each channel has its own individual neutral conductor terminal
- ✓ A blue LED indicates the module's operating status
- ✓ Green LEDs (one for each input) indicate the input status
- ✓ 4 inputs, electrically isolated from the backplane bus

Digital input module, AC 230 V, per channel N 4x

Im Lieferumfang sind bereits der passende Frontstecker für die Verkabelung und ein Basismodul enthalten. Das Modul verfügt

über 16 digitale Eingänge in m-lesender Ausführung.

The scope of delivery already includes the appropriate front connector for the cabling and a base module. The module has 4 digital inputs for 230V AC.

General information

Order number	600-211-0BD01
Article name	DI 4x AC 230 V, per channel N, type 1
Scope of delivery	DI 4x AC 230 V, per channel N, type 1
Dimensions (DxWxH)	110 x 14 x 73 mm
Weight	Approx. 70 g
Number of inputs	4
Power dissipation	Max. 7.6 W
Input characteristic curve	Type 1, EN 61131-2
Input frequency	50 Hz / 60 Hz
Hot-swap capable	Yes
Hot-swap capable	Yes

Electrical isolation

from the backplane bus	Yes
Between the channels	Yes

Current draw

External	Max. 0 mA
Internal	Max. 22 mA

Input voltage

For signal "0"	0 V ... 40 V
For signal "1"	79 V ... 253 V
For signal "1"	79 V ... 253 V

Ambient conditions

Ambient temperature	0 °C ... +60 °C
Transport and storage temperature	-20 °C ... +80 °C
Relative air humidity	95 % r H without condensation
Protection rating	IP 20

Certifications	CE, UL
----------------	--------

UL

Surrounding Air Temperature	0 °C ... +60°C
Pollution degree	2

CE

Noise immunity	DIN EN 61000-6-2 "EMC Immunity"
Interference emission	DIN EN 61000-6-4 "EMC Emission"
Vibration and shock resistance	DIN EN 60068-2-6:2008 „Vibration“, DIN EN 60068-2-27:2010 „Shock"

© Helmholtz GmbH & Co. KG | Hannberger Weg 2 | 91091 Großenseebach | Germany
Phone +49 9135 7380-0 | Fax +49 9135 7380-110 | info@helmholz.com | www.helmholz.com

We reserve the right to make changes without notice.
Errors and omissions excepted.