



Features

- ✓ 300 mA output voltage per channel
- ✓ A blue LED indicates the module's operating status
- ✓ Green LEDs (one for each output) indicate the outputs' states
- ✓ 8 outputs, electrically isolated from the backplane bus

Digital-output-module, DC 24 V, 300mA, sink 8x

Digital output modules for the modular fieldbus IO system TB20.

Note: Individual modules cannot be combined with IO systems from other

manufacturers.

The scope of delivery already includes the appropriate front connector for the cabling and a base module. The module has 8 digital

m-switching (sinking) outputs with an output power of up to 300mA.

General information

Order number	600-220-0DH01
Article name	DO 8x DC 24 V, 300 mA, sink
Scope of delivery	DO 8x DC 24 V
Dimensions (DxWxH)	110 x 14 x 73 mm
Weight	approx. 70 g
Number of outputs	8
Power dissipation	Max. 2.5 W
Output short-circuit protection	Electronic, for each individual channel
Inductive cutoff voltage limit	-48 V
Hot-swap capable	Yes
Hot-swap capable	Yes

from the backplane bus	Yes
Between the channels	No

Supply voltage UP, US

Rated value	-24 V DC
Ripple USS	Max. 3.6 V
Permissible range (with ripple)	20 ... 30 V
Voltage for t < 10 ms	50 V

Output current

Rated value	300 mA
Leakage current	max. 0,5 mA

Electrical isolation

Current draw

External	Max. 40 mA + load
Internal	Max. 35 mA

Ambient conditions

Ambient temperature	0 °C ... +60 °C
Transport and storage temperature	-20 °C ... +80 °C
Relative air humidity	95 % r H without condensation
Pollution degree	2
Protection rating	IP 20
Certifications	CE, UL

UL

Surrounding Air Temperature	0 °C ... +60°C
Pollution degree	2

CE

Noise immunity	DIN EN 61000-6-2 "EMC Immunity"
Interference emission	DIN EN 61000-6-4 "EMC Emission"
Vibration and shock resistance	DIN EN 60068-2-8:2008 "Vibration", DIN EN 60068-27:2010 "Shock"