



Features

- ✓ Measuring ranges 0 ... 20 mA, 4 ... 20 mA, ± 20 mA, individually configurable for each channel
- ✓ Measurement resolution: 11 bit + sign
- ✓ Suitable for 2- and 4-wire transmitters
- ✓ Diagnostic messages
- ✓ Wire break detection (for 4 ... 20 mA)
- ✓ Limit value alarms for each channel
- ✓ A bi-color LED (blue/red) indicates the module operating status and any malfunctions
- ✓ 2 analog inputs for measuring current, electrically isolated from the backplane bus
- ✓ 2 process input words

Analog-input-module, I, 12 Bit 2x

Analog input modules for the modular fieldbus IO system TB20.

Note: Individual modules cannot be combined with IO systems from other manufacturers.

The scope of delivery already includes the appropriate front connector for the cabling and a base module. The module has 2 analog inputs.

Parameters for the module:

Diagnostic alarm: On | Off
 Overflow / underflow diagnosis: On | Off
 Representation values: SIMATIC® S7 | SIMATIC® S5

Parameters for each channel:

Wire break detection (only for 4 ... 20 mA): On | Off

Interference frequency suppression: None | 10 Hz | 50 Hz | 60 Hz | 400 Hz

Measuring ranges: Deactivated | 0 ... 20 mA | 4 ... 20 mA | ± 20 mA
 Limit value alarms enabled: On | Off
 Upper/lower limit: 16 bit analog value (± 27648)

* SIMATIC is a registered trademark of Siemens AG.

General information

Order number	600-250-4AB01
Article name	AI 2x I, 0/4...20 mA, ± 20 mA, 12 bit
Scope of delivery	AI 2x I, 0/4...20 mA, ± 20 mA, 12 bit
Dimensions (DxWxH)	110 x 14 x 73 mm
Weight	Approx. 70 g
Number of inputs	2
Power dissipation	Max. 0.7 W
Hot-swap capable	Yes

from the backplane bus	Yes
Between the channels	No

Current draw

External	Not needed
Internal	Max. 95 mA

Measuring

Measuring ranges / load resistance	0 ... 20 mA / 50 ohms,
------------------------------------	------------------------

Electrical isolation

	4 ... 20 mA / 50 ohms, ±20 mA / 50 ohms
Measuring method	Integration
Measurement resolution	11 bit + sign
Interference frequency suppression	None 10 Hz 50 Hz 60 Hz 400 Hz
Refresh rate / conversion rate	Number of active channels x conversion time + 16 ms for wire break detection when activated. The conversion time will depend on the interference frequency suppression: None: 8 ms 400 Hz: 45 ms 60 Hz: 109 ms 50 Hz: 128 ms 10 Hz: 342 ms
Diagnoses	Upper measuring range limit exceeded (overflow), lower measuring range limit fallen below (underflow), wire break (for 4 ... 20 mA only), parameter assignment error
Process alarms	Upper and lower limit per channel

Error limits

Operational error limit in the entire temperature range	±0.5 % relative to the nominal range
Basic error limit at 25 °C	±0.3 % relative to the nominal range
Temperature error	±0.005 %/K relative to the nominal range

Linearity error	±0.05 %/K relative to the nominal range
Repeating accuracy in steady state at 25 °C	±0.05 %/K relative to the nominal range
Parameter configuration length	12 bytes
General error indicator	Red LED
General error indicator	Red LED

Ambient conditions

Ambient temperature	0 °C ... +60 °C
Transport and storage temperature	-20 °C ... +80 °C
Relative air humidity	95 % r H without condensation
Protection rating	IP 20
Certifications	CE, UL

UL

Surrounding Air Temperature	0 °C ... +60°C
Pollution degree	2

CE

Noise immunity	DIN EN 61000-6-2 "EMC Immunity"
Interference emission	DIN EN 61000-6-4 "EMC Emission"
Vibration and shock resistance	DIN EN 60068-2-6:2008 „Vibration“, DIN EN 60068-2-27:2010 „Shock“