



## Features

- ✓ Measuring ranges 0 ... 24 V, ±24 V, individually configurable for each channel
- ✓ Measurement resolution: up to 11 bits + sign
- ✓ Diagnostic messages
- ✓ Limit value alarms for each channel
- ✓ A bi-color LED (blue/red) indicates the module operating status and any malfunctions
- ✓ 4 analog inputs for measuring voltage, electrically isolated from the backplane bus
- ✓ 4 process input words

## Analog-input-module, U 24V, 12 Bit 4x

Analog input modules for the modular fieldbus IO system TB20.

**Note:** Individual modules cannot be combined with IO systems from other manufacturers.

The scope of delivery already includes the appropriate front connector for the cabling

and a base module. The module has 4 analog inputs.

### Parameters for the module:

Diagnostic alarm: On | Off  
Overflow / underflow diagnosis: On | Off  
Representation values: SIMATIC® S7 | SIMATIC® S5 | INT16

### Parameters for each channel:

Interference frequency suppression: None | 10 Hz | 50 Hz | 60 Hz | 400 Hz

Measuring ranges: Deactivated | 0 ... 24 V | ±24 V

Limit value alarms enabled: On | Off  
Upper/lower limit: 16 bit analog value (+27648)

\* SIMATIC is a registered trademark of Siemens AG.

## General information

Order number	600-252-4CD01
Article name	AI 4x U, ±24 V, 0-24 V, 12 bits
Scope of delivery	AI 4x U, ±24 V, 0-24 V, 12 bits
Dimensions (DxWxH)	110 x 14 x 73 mm
Weight	Approx. 70 g
Number of inputs	4
Internal	Max. 95 mA
Power dissipation	Max. 0.7 W
Parameter configuration	
length	22 bytes
General error indicator	Red LED
Hot-swap capable	Yes

Hot-swap capable	Yes
------------------	-----

## Electrical isolation

from the backplane bus	Yes
Between the channels	No

## Measuring

Measuring ranges / load resistance	0 ... 24 V/30 kohm, ±24 V/30 kohm
Measuring method	Integration

Measurement resolution	11 bit + sign
Interference frequency suppression	None   10 Hz   50 Hz   60 Hz   400 Hz
Refresh rate / conversion rate	Number of active channels x conversion time +16 ms for wire break detection for each channel when activated. The conversion time will depend on the interference frequency suppression: None: 8 ms 400 Hz: 45 ms 60 Hz: 109 ms 50 Hz: 128 ms 10 Hz: 342 ms
Diagnoses	Upper measuring range limit exceeded (overflow), lower measuring range limit fallen below (underflow), parameter assignment error
Process alarms	Upper and lower limit per channel

## Error limits

Operational error limit in the entire temperature range	±0.5 % relative to the nominal range
Basic error limit at 25 °C	±0.3 % relative to the nominal range
Temperature error	±0.005 %/K relative to the nominal range

Linearity error	±0.05 %/K relative to the nominal range
Repeating accuracy in steady state at 25 °C	±0.05 %/K relative to the nominal range

## Ambient conditions

Ambient temperature	0 °C ... +60 °C
Transport and storage temperature	-20 °C ... +80 °C
Relative air humidity	95 % r H without condensation
Protection rating	IP 20
Certifications	CE, UL

## UL

Surrounding Air Temperature	0 °C ... +60°C
Pollution degree	2

## CE

Noise immunity	DIN EN 61000-6-2 "EMC Immunity"
Interference emission	DIN EN 61000-6-4 "EMC Emission"
Vibration and shock resistance	DIN EN 60068-2-6:2008 „Vibration“, DIN EN 60068-2-27:2010 „Shock“